

Safety and Warning Information



Hazardous Voltage:

Only Authorized Personnel may service this equipment.



Connect the DIN Rail via the End Clamp (2A09) to Protective Earth ground with low impedance. The modules are grounded to PE when they are snapped onto the DIN Rail. The End Clamps will accept wire sizes from 12 to 24 AWG.



Do not connect this supply to EOTec 2000 PLC Modules or Ethernet Modules. This supply is for use with the FOT and FOR Analog Link Modules ONLY.

Further technical information can be obtained by contacting Weed Instrument Co., Inc., Fiber Optic Products Group.

Phone: 1.800.880.9333
512.434.2850

Fax: 512.434.2851

Email: fiberop@weedinstrument.com

Visit: www.weedinstrument.com

Important Notice - Before utilizing the product, the user should determine the suitability of the product for its intended use. The user assumes all risk and liability in connection with such use. WEED INSTRUMENT'S WRITTEN WARRANTY FOR THE PRODUCT IS MADE IN LIEU OF ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. The user's exclusive remedy for breach of Weed Instrument's written warranty shall be the repair or replacement of such quantity of product which is proven to be defective. In no case shall Weed Instrument be liable for any special, incidental, or consequential damages based upon breach of contract, negligence, strict liability or other legal theory.

Weed Instrument Co., Inc.
Round Rock, Texas, USA


www.weedinstrument.com

Publication Number: RM0900159 Rev. 11/03



Weed Instrument

Fiber Optics



2A56

EOTec 2000 Analog Link
Power Supply Module

Installation Instructions



Compatible with:

**EOTec 2000 FOT and FOR
Analog Links**

**85 to 240 VAC, 50/60 Hz;
85 to 140 VDC Input**

**Supplies 24 VDC @ 425mA operating
power output to analog link BUS
Interconnections**

DIN Rail Mounting

Installation on DIN rail:

Place the top lip of the module's DIN rail mounting channel onto the DIN rail. Push the lower portion of the module towards the mounting surface until it "clicks" and locks into place. Firmly slide the modules together such that the module sides are touching. This ensures a good connection of the integrated BUS interconnection at the rear of the modules. Install End Clamps (Model 2A09) to both sides of the module bundle to prevent accidental unplugging of the BUS interconnections. The End Clamps also provide convenient screw terminals for connecting the DIN rail to Protective Earth (PE) ground.

Removal from DIN rail:

Remove the End Clamps from the module bundle. Disconnect the BUS interconnections by sliding the modules at least 1/2" apart from each other on the DIN rail. Insert a screwdriver into the rectangular hole in the metal mounting latch at the bottom of the module. Pushing up on the screwdriver's handle causes the latch to move downward and disengages it from the DIN rail. Tilt the module up and lift it off of the DIN rail.

Connections

Power to the unit is supplied via connections at the top-front of the module. A pluggable, cage-clamp, screw terminal block is connected to the supply voltage as follows (terminals numbered from left to right):

Terminal 1	AC Line or DC (+)
Terminal 2	no connection
Terminal 3	no connection
Terminal 4	AC Neutral or DC (-)

Protective Earth (PE) ground is connected to the module via the DIN rail and the Model 2A09 End Clamps (two supplied). The End Clamps will accept wire sizes from 12 to 24 AWG.

LED Indicators

The green "PWR" LED indicator will illuminate whenever the 24Vdc BUS operating power is available to the other modules in the analog link.

Specifications

Mounting:	35mm DIN Rail
Weight:	< 9 oz (250g)
Power Requirements:	85 to 240Vac, 50/60 Hz, 85 to 140Vdc, 250 mA
Output to Integrated BUS Interconnections:	24Vdc, 425mA
Screw Terminals:	Pluggable, cage-clamp, screw terminal block Accept 12 to 24 AWG
Input Fuse:	250V, 400mA,slow-blow 5 x 20mm Littlefuse # 218.400 Always replace fuse with the same type and rating
Operating Range	
Temperature:	-40 to 85°C
Relative Humidity:	0 to 95% (non-condensing)
Flammability:	UL 94V-0