

6C15 Electrical Interface Module



The 6C15 Module provides electrical interface for Allen-Bradley DH-485TM communications by conditioning the electrical signals supplied to and from the Allen-Bradley equipment for transmission over the fiber optic network. The module obtains operating power and interconnects to other modules in the EOTec 6000 Modem via the integrated backplane of the Model 6A02 Modular Rack.

The simplest modem configuration consists of a Power Supply, an Electrical Interface, and an Optical Interface Module. However, additional modules may be added to configure Daisy Chain, Star, Self-Healing Ring topologies and provide Redundancy. A maximum combination of five optical or electrical modules may be connected together in one modem.

SPECIFICATIONS

Mechanical:

Mounting: Slot 5 of the 6A02 Modular Rack with the Master/Slave switch in the Master position
Slot 1 through 4 of the Modular Rack with the switch in the Slave position

Weight: < 7oz (200g)

Baud Rate: 19.2K Baud

Copper Cable Connector: .375" Screw Terminal Barrier Strip

Copper Cable End Termination: Internal, 120 Ohms

Maximum Allen-Bradley Units and Cable Length Supported per Module: 1 Device, 200 feet

Power Indicator: Green LED

Ambient Conditions: -40°C to 80°C Storage
0°C to 70°C Operational
0 to 90% Relative Humidity Non-Condensing

